AUTOMOTIVE TOUCH-UP AEROSOLS

DESCRIPTION AND USES

Rust-Oleum® Automotive Touch-Up Paint is a premium acrylic finish designed to provide fast dry, excellent coverage and maximum durability. It is available in a wide variety of factory matched colors. It is suitable for use on trim and accessories. Touch-Up Aerosols feature an advanced spray system that allows you to spray at any angle, even upside down for those hard to reach areas. A comfort spray tip with a wider finger pad reduces fatigue caused by continuous spraying.

PRODUCTS

SKU (8 ounce spray)	Description
ATU10002	Arcadia Green
ATU10003	Hamstead Green
ATU10004	Avigon Blue
ATU10005	Milano Red
ATU10006	Arctic Silver
ATU10007	Black
ATU10008	Seattle Silver
ATU4001	Radiant Silver
ATU4002	Forrest Green
ATU4003	Flash Red
ATU4004	Light Champagne
ATU4005	Bright Silver
ATU4006	Champagne Pearl
ATU4007	Charcoal Gray
ATU4008	Garnet
ATU4009	Radiant Red
ATU4010	Claret Red
ATU4011	Deep Cranberry Pearl
ATU4012	Bright White
ATU4013	Spruce
ATU5000	Deep Jewel Green
ATU5001	Silver
ATU5002	Dark Blue
ATU5003	Oxford White
ATU5004	Shadow Gray
ATU5005	Royal Blue
ATU5006	Toreador Red
ATU5008	Wimbledon White
ATU5008	Silver
ATU5009	Cardinal Red
ATU5010	Medium Blue
ATU5011	Charcoal Silver
ATU5012	Blue
ATU5013	Cayman
ATU5014	Special White
ATU5015	Dark Jade
ATU5016	Medium Charcoal
ATU5017	Sunburst Gold
ATU5018	Electric Currant Red
ATU5019	Mocha Frost
ATU5020	Twilight Blue
ATU5021	Arizona Beige
ATU6000	White
ATU6001	Ultra Silver
ATU6002	Black
ATU6003	Classic White
ATU6004	Cherry Red
ATU6005	Victory Red
ATU6006	White
ATU6007	Dark Blue
ATU6008	Black
ATU6009	Storm Gray
ATU6010	Light Slate
ATU6011	Emerald Green
ATU6012	Indigo
ATU6013	Bright Red
ATU6014	Light Blue
ATU6015	Silver
ATU6016	Garnet Red
ATU6017	Gray
ATU6018	Pewter
ATU6019	Bright Red
ATU6020	Arctic White

PRODUCTS

SKU (8 ounce spray)	Description
ATU6021	Light Driftwood
ATU6022	Bright White
ATU6023	Bright Aqua
ATU6024	Light Blue
ATU6025	White
ATU6026	Medium Garnet Red
ATU6027	Medium Quasar
ATU6028	Charcoal
ATU6029	Ultra Marine Blue
ATU6030	Medium Green
ATU6031	Repair Gold
ATU6032	Red
ATU6033	Autumn Maple
ATU6034	Gunmetal
ATU6035	Dark Cherry
ATU7000	Super White
ATU7001	Burgundy Pearl
ATU7002	Silver Frost
ATU7003	Orange Mist
ATU7004	Cherry Red Pearl
ATU7005	Cloud White
ATU8000	Brilliant Black
ATU8001	Graceful Red
ATU9000	Super White II
ATU9001	Platinum Silver
ATU9002	Silver
ATU9003	Classic Green Pearl
ATU9004	Super Red OII
ATU9005	Crème
ATU9006	Yellow
ATU9007	Almond Beige pearl
ATU9008	Black
ATU9009	Cashmere Beige
Cc1000	Clear Coat
PR2000	Gray Primer
UNI1000	Universal Black
UNI1001	Universal Flat Black
UNI1002	Universal Black Metallic
UNI1003	Instant Chrome

PRODUCT APPLICATION

PAINTING CONDITIONS

Use outdoors or in a well ventilated area such as an open garage. Use when temperature is between 60-90°F (16-32°C) and humidity is below 60% to ensure proper drying. Do not apply to surfaces that, when heated, exceed 200°F (93°C). Avoid spraying in very windy and dusty conditions. Cover surrounding area to protect from spray mist.

PRIMING

Use of a Rust-Oleum Automotive Primer (#PRI2000) provides added corrosion protection, enhances adhesion and hiding, and is especially recommended for heavily rusted surfaces or if bare metal is exposed. Allow primer to dry 1 hour before applying Rust-Oleum Automotive Touch-Up Paint.

Form: GDH-199
Rev.: 102213

PRODUCT APPLICATION (cont.)

SURFACE PREPARATION

Wash the surface with a commercial detergent, or other suitable cleaning method to remove dirt. Rinse with fresh water and dry with a clean cloth. For best results, remove all oil, grease, wax and petroleum based materials with Rust-Oleum Wax & Tar Remover. Remove loose paint and rust with a wire brush or sandpaper. Lightly sand glossy surfaces. **WARNING:** If you scrape, sand, or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to www.eps.gov/lead**.**

APPLICATION

Shake can vigorously for one minute after the mixing ball begins to rattle. If mixing ball fails to rattle DO NOT STRIKE CAN. Contact Rust-Oleum. Shake often during use. Hold can 8-10" from surface and spray in a steady back-and-forth motion, slightly overlapping each stroke. Keep the can the same distance from the surface and in motion while spraying. Apply 2 or more light coats a few minutes apart. Do not use near open flame.

DRY & RECOAT

Dry and recoat times are based on 70°F (21°C) and 50% relative humidity. Allow more time at cooler temperatures. Dries to the touch in 30 minutes, to handle in 1 hour and can be recoated at any time.

CLEAN-UP

Wipe off tip when finished. Clean up wet paint with acetone or lacquer thinner. Properly discard empty container. Do not burn or place in home trash compactor.

CLOGGING

If the valve clogs, twist and pull off spray tip and rinse in a solvent such as acetone or lacquer thinner. Do not insert any object into can valve opening.

TECHNICAL DATA

AUTOMOTIVE TOUCH-UP AEROSOLS

PHYSICAL PROPERTIES

		AUTOMOTIVE TOUCH-UP AEROSOLS
Resin Type		Modified Acrylic
Pigment Type		Varies with Color
Solvents		Acetone, Acetates, Ketones, and Aromatic Hydrocarbons
MIR		1.90 Max
Fill Weight		8 ounces
Recommended Dry Film Thickness (DFT) Per Coat		1.5-2.5 mils (37.5-62.5µ)
Practical Coverage at Recommended DFT		10-12 sq. ft./can (0.90-1.09 m^2/can)
Dry Times at 70°F (21°C) and 50% Relative Humidity	**Touch**	30 minutes
	Handle	1 hour
	Recoat	At any time
Dry Heat Resistance		200°F (93°C)
Shelf Life		5 years
Flash Point		-156°F (-104°C)
Safety Information		For additional information, see MSDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.

RUST-OLEUM BRANDS

Rust-Oleum Corporation
11 Hawthorn Parkway
Vernon Hills, Illinois 60061
An RPM Company

Phone: 877•385•8155
www.rustoleum.com

Form: GDH-199
Rev.: 102213